37 ft 2006 Southerly 115, ARCTIC TERN £138,500 Tax: Paid, United Kingdom

Wallasea Island, Essex, United Kingdom













Boat Details

Price:

Southerly Cruiser 2 Guest Cabins: Make: Class: 115 **Fiberglass** 1 Hull Material: Guest Heads: Model: 2006 **Shaft Drive** Fuel Type: **Diesel** Year: Drive Type: 37 ft 12 ft Max Draft: 8 ft 2 in Beam: Length:

£138,500 Boat Location: Wallasea Island, Essex,

United Kingdom

Condition: Used Name: ARCTIC TERN

Adrian Webb | Southerly Brokerage & Service

Itchenor, Chichester, West Sussex, United Kingdom

Tel: **+44 (0)1243 512611**

adrian.webb@northshore.co.uk www.southerlybrokerage.com

Description

The Southerly 115 Mk IV has benefited greatly from the class's continual development since the first Southerly 115 was built.

She has good cruising performance and has proven herself to be an excellent and safe family cruising yacht, whether it be for short passage or long passage making.

The interior is light and spacious and the aft cabin is simply wonderful. The interior design works well either at anchor or at sea.

Some of the many upgrades incorporated into Artic Tern over the early Southerly 115s include better interior headroom and standard of finish, a deeper and heavier keel giving improved sailing performance and twin rudders for even better steering under sail and power.

The swing keel is very well proven and gives tremendous flexibility to ones cruising. She can sail in under 3 feet of water and can even dry out on a suitable surface. The keel can be used anywhere between up and down.

She has up to 7 berths. There is are 2 singles or a double forward, a double aft and a double conversion in the saloon plus another single as well.

A full extensive upgrade and service was undertaken by Northshore in 2022/2023 (schedule available)

Artic Tern will be ideal for your weekending or for longer living aboard whilst extensive cruising.

Information & Features

2006 Yanmar 3JH3E (Engine 1)

Engine Type:InboardPower:40 hpFuel Type:DieselPropeller Type:3 BladeDrive Type:Shaft DrivePropellerBronze

Material:

Dimensions

LOA: 37 ft Max Bridge 50 ft 6 in

Clearance:

 LWL:
 29 ft 2 in
 Min Draft:
 2 ft 4 in

 Beam:
 12 ft
 Max Draft:
 8 ft 2 in

Weights

Displacement: 17,262 lb

Accommodations

Guest Cabins: 2
Guest Heads: 1

Other

Warranty: None
Hull Shape: Monohull

Dimensions

Length Overall	11.25m	37ft 10ins
Length Waterline	8.90m	29ft 2ins
Beam	3.66m	12ft Oins
Draught (keel up)	0.71m	2ft 4ins
Draught (Keel down)	2.48m	8ft 2ins
Displacement	7,830kgs	17,262lbs
Ballast weight	2,250kgs	4,962lbs
Keel weight	1,195kgs	2,635lbs
Total ballast	3,445kgs	7,597lbs
Air Draught	15.40m	50ft 6ins

Hull construction

Heavy duty GRP moulding, hand laid up to Northshore's Nordseal laminating system incorporating multi-axial and unidirectional reinforcements. Thickness increases progressively towards the keel area. The keel box is an integral part of the hull layup and sandwich construction stiffening runs the entire length of the hull topsides All main bulkheads are bonded into the hull at the layup stage.

Hull topside gelcoat colour: Ivory White 9010

Underwater gelcoat colour: Clear Boot top colour: Oxford Blue Style stripe colour: Oxford Blue

Antifouling: Hull Coppercoated, keel conventional antifouling paint (2023 by Northshore)

Rubbing strake: Teak rubbing strakes with stainless steel rubbing bands

Deck construction

Hand laid up GRP sandwich type construction using balsa core stiffening with plywood in high stress areas where fittings are positioned, heavily stressed area are additionally reinforced with unidirectional glass reinforcement. The hull is bonded to the deck through the entire length and to all main bulkheads resulting in a strong and integrated unit. A teak capping is fitted to the hull and deck joint upstand.

Deck gelcoat colour: Ivory white 9010

Ring deck: Two tone (Biscuit)

Swing Keel

The fixed ballast is an iron casting which acts as a grounding plate and as transverse stiffening to the keel unit. It is fitted into a recess in the hull in the area of the keel box with stainless steel studs. The aerofoil swing keel is cast iron and incorporates a stainless steel pivot at the leading edge, The swing keel is raised and lowered by a hydraulic ram powered by an electrically driven pump with a hand operated back up. All hydraulics are easily accessible for maintenance. A keel control switch and gauge showing keel position are fitted at the wheel pedestal. Supplied with a removeable stainless steel pin to enable the keel to be locked in the "up" position.

New keel pennant and LED display fitted 2023

Engine room and propulsion

Yanmar 3JH4E 40hp, 3 cylinder fresh water cooled diesel engine with reduction/reverse gearbox, serviced 2023

60amp alternator

Bronze stern tube with water lubricated stern gland

Stainless steel propeller shaft

Bronze three blade Variprop feathering propeller

Ambassador AM10 rope cutter fitted

Substantial skeg fitted on centreline to protect propeller and rudders when yacht is dried out.

Stainless steel fuel tank in sail locker with sediment trap and line filter, 225L/50gal capacity.

Non metallic water strainer with removeable filter

12 volt electric ventilator

Extractor fan

Sound deadening to engine box

Opening doors to engine box for access

Automatic CO² fire extinguisher fitted in engine space

Bowthruster

75Kg tunnel bow thruster fitted with joystick control at steering pedestal, service 2023

Electrics

12 volt system

Three heavy duty batteries, charged from engine alternator, one for engine start, two for domestic use, NEW in 2021

NASA battery monitor BM-1

Mastervolt automatic battery charger, NEW in 2021

Battman unit to monitor charge/discharge of domestic batteries

Isolating switches

Cabin lighting throughout

Reading light over bunks

Chart light over navigation table

Full navigation light system incorporating, bow lights, stern light, masthead tri-colour light with all round white anchor light, deck floodlight and steaming light

Circuit breakers on main switch panel board

12V interior socket (Cigarette type) fitted at chart table

Lightning master fitted at masthead with grounding plate fitted to hull

240V ring main system, with 3 double UK outlet sockets, earth leak circuit breaker and connecting cable with plug for connecting to shore power. 1Kw Immersion heater fitted to calorifier

Electronics and navigation

Radar reflector fitted on mast

Raymarine ST60+ speed, depth and wind indicators mounted in instrument pod

Raymarine ST60 graphic display fitted at steering pedestal

Raymarine autopilot with Lewmar Whitlock Mamba rotary drive, St6001+ displays fitted in cockpit and at chart table

Raymarine C120 chart plotter display fitted at chart table, serviced 2023

Raymarine Axion 9Pro, with AIS and Raymarine 28-XG chart fitted at cockpit, fitted new in 2023

18" Raymarine Raydome fitted to stainless steel arch

Raystar 125 satellite differential GPS antenna fitted to stainless steel arch

Fishfinder module

Navtex 6 Plus c/w antenna mounted on stainless steel arch

Vertex VHF, with fog horn/loud hailer fitted to mast and extension handset fitted in cockpit

New VHF antenna fitted 2023

GlobalFix™ V4 EPIRB EPIRB Cat 2 in saloon, new in 2023

Engineering

Hot air heating system with three outlets

Keel cooled evaporator plate, with sintered keel cooler, fitted to ice box

Greyline 85ASU front opening refrigerator

Radio/CD stereo system with two speakers in saloon

2 Waterproof speakers fitted to cockpit

15" LCD flat screen TV fitted to saloon bulkhead with Glomex TV antenna fitted to stainless steel arch

Holding tank system fitted

Microwave fitted in aft end of galley facing inboard

Water systems and pumps

Pressurised hot and cold water system

Mixer tap to galley

Mixer tap to heads compartment

Aquafilta water filter fitted

Patay Helford chrome freshwater hand pump fitted at galley sink

Stainless steel water tank under aft end of dinette, 205L/45gal capacity

Additional water tank fitted under Galley

Hot water provided by engine calorifier unit

Deck shower with hot and cold water fitted to cockpit on starboard side

Electric sump pump to shower tray

One manual bilge pump

One electric submersible bilge pump

Steering

Semi-balanced twin rudders

Pedestal mounted Lewmar folding wheel, fitted new 2023

Lewmar Whitlock Mamba torque tube and gearbox steering system

Single lever engine control at pedestal

Emergency steering tiller arm

6" main steering compass

Spars and rigging

Selden masthead rid

Double spread rig

Selden anodised aluminium spars finished in silver

Internal halyards

1 x 19 stainless steel wire standing rigging with swage toggle-fork rigging screws, fitted new in 2023

Furlex headsail reefing system

Single line reefing led aft to cockpit for mainsail

Kicker, main halyard, topping lift, outhaul and reefs led aft

Genoa halyard at mast

Burgee and signal halyard

Sail controls lead aft across the coachroof

Lewmar size 8 winch fitted on lower mast

Telescopic spinnaker pole with vertical mast stowage and topping lift and down hauls

2 folding mast steps 1M down from top of mast

Removable stainless steel bowsprit

Sails

Dacron sails

UV protect strip to foresail

Fully battened mainsail with Selden MDS cars

Stackpack system for mainsail in blue canvas with lazy jack system at mast

Furling asymmetric cruising chute

Cockpit

Centre cockpit

Self-draining

Laid teak to cockpit seats

Teak grating on cockpit sole

Telescopic stern boarding ladder

Large cockpit locker

Drained gas bottle stowage in cockpit locker

Two cave lockers in cockpit coamings

Acrylic main hatch with washboard

Instrument panel above hatchway

Two winch handle pockets

Steering pedestal

Extended pod for instruments fitted new 2023

Lewmar Whitlock steering pedestal

Two safety harness eyes

Sprayhood with integral handle in blue canvas, Renewed 2019

Full cockpit enclosure to zip to sprayhood, with roll up sides and entrance across aft deck, Renewed 2019

Two Wichard LYF safe jackstays, new in 2023

Deck fittings and loose gear

Cleats forward and aft raised

Spring clats amidships with stainless steel chafe guards

Stainless steel stemhead fitting with twin bow roller

GRP foredeck anchor locker with reinforced shelf for windlass

Stainless steel spit pulpit (for bow boarding) incorporating navigation light bracket

Stainless steel stanchions and guardwires, with gates port and starboard

Stainless steel pushpit with seats, incorporating stern gate, navigation light bracket and ensign socket, with integral stainless steel arch, for antennas and solar panels, and lift eyes for outboard motor, hinged on forward edge

To SM50S solar panels mounted on arch

Fuel and water deck fillers

Holding tank pump out fitting

Genoa tracks with single car and plunger control stops

Genoa sheet turning blocks to take Furlex control light

Mainsheet track with control lines leading aft to cockpit

Three rope clutches each side for running rigging

Two Lewmar 44ST winches on coaming

Two Lewmar 16 winches at companionway

Stainless steel grab handles on either side of coachroof

Lewmar Pro-Fish 1000 anchor, 12 volt windlass and footswitch, new in 2023

15Kg Bruce anchor

30 Metres of 8mm chain

30M of warp

Two fire extinguishers, new in 2023

One fire blanket

Yellow horseshoe lifebuoy with flashing light

Seago 4 man cannister liferaft in stowage cradle, NEW in 2020

PVC coated wire harness lifeline jackstays, port and starboard

Teak pad for outboard engine fitted to pushpit

Rutland WG1200 windcharger and digital display, new in 2023

3 Person dinghy with cover

Outboard, 3.5hp two-stroke

Windows, hatches and ventilation

Two opening deck hatches, size 60, one to forecabin, one to aft cabin

Two opening hatches size 20 over galley and chart table

Four opening ports in aft cabin

Dorade ventilator over saloon

Ventilators in heads and galley

Acrylic main companionway hatch

Coachroof windows and hull ports are partially reflective toughened glass, bonded into recessed on the GRP mouldings

Internal joinery and furnishings

Interior joinery is finish in solid wood and faced marine quality plywood

Linings are fabric covered plywood or GRP as appropriate.

Cabin soles are teak and holly striped non-slip laminate

Wood: American Cherry

Galley worktop: Natural acrylic stone, Gemini

Heads countertop: Nordstone White

Fabric, saloon: Melville 3288/07 Blue Haze Fabric, cabins: Morely 3823/07 Blue Haze

Fabric, navigation seat: Navy plain

Curtains: Vellum

Blinds: Concertina blinds fitted to raised coachroof windows

Accommodation

The layout is in accordance with the general arrangement drawing

There are a total of seven berths with two I the forecabin, two in the aft cabin and three in the saloon (double berth conversion and a single settee)

Galley

Raised Galley to port

Twin stainless steel sinks

Hot and cold pressurised water

Natural acrylic stone worktop

Fiddles surrounding worktops

Ice box with top access

Stainless steel grab rail to worktop

Fully gimballed gas cooker with two burners, grill and oven. Fail safe devises on all burners

Gas cut off tap

Gas system full services and certified in 2023

Gas alarm, new in 2023

Crockery stowage

Cupboard for utensils and food

Cutlery drawer

Opening hatch

Saloon

Dinette seating arrangement to port

Table will extend to starboard to maximise seating

Lockers under dinette

Stainless steel mast support. Table slides and can drop to convert to a double berth

Shelves both sides of saloon

Stowage behind

Full length single settee to starboard

Bookshelf

Bottle stowage

Recessed lights under side decks

Two overhead lights

Four fixed hull ports

Curtains to hull ports

Navigation area

Chart table to starboard with excellent visibility

Instrument console forward of chart table

Chart stowage under hinged lid

Book stowage below

Helmsman seat with stainless steel grabrail Large stowage under seat Chart light Main electrical switch panel Overhead deck light Opening hatch Aft cabin Two large single berths on either side with infill panel to make very large double berth Three overhead lockers aft Two hanging lockers Seat to port Stowage under berth Two reading lights Two overhead lights Two fixed hull ports Four opening ports in coamings Curtains to hull ports Opening deck hatch Access to sterntube through cabin sole Aft Cabin en-suite with marine toilet and wash basin Main Heads Heads compartment to starboard of companionway Marine toilet Hinged seat to cover marine toilet Washbasin with Nordstone surround Shower head mixer tap Hot and cold pressurised water Stowage lockers Shower fixing Electric shower tray drain pump Grating to shower tray Mirror Fixed light Waterproof toilet roll holder

Oilskin hanging space

Forecabin

Two full size overlapping berths

Stowage under

Full length shelf to port

Twin lockers under foredeck forward

Two fixed hull ports

Opening deck hatch

One overhead light

Two reading lights

Curtains to portlights

Disclaimer

The Company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents, or his surveyors, to investigate such details as the buyer desires validated. This vessel is offered subject to prior sale, price change, or withdrawal without notice.













































